

Date: 24/07/2020

FULL DETOX PRO

ADVANCED FUEL ADDITIVE

DESCRIPTION

Complete multifunctional fuel additive for petrol and diesel engines. Specially designed for all diesel and petrol engines including the newest generations with high-pressure injection for:

- Powerful cleaning of the fuel injection system.
- Active and effective clean-up and keep clean of Diesel Particle Filter (DPF), Gasoline Particle Filter (GPF) and the variable vanes of the turbo charger.

BASIC BENEFITS

- · Fuel savings.
- 1 product for diesel and petrol treatments.
- · Trouble-free functioning of the DPF/GPF & Catalytic system.
- · Smoother engine running.
- · Restored power and dynamics.
- Reduction of smoke and CO2 emissions.
 Helps to pass the emission test on the car inspection.
- · Improved engine reliability.

PROPERTIES

- · Cleans fuel injection system and pumps.
- · Accelerates the regeneration of the Diesel/Gasoline Particle Filter.
- · Protects the intake system and EGR-valve from deposits.
- Keeps the turbo and exhausts system clean.

APPLICATION

Use at regular service or when problems appear. XENUM specialists recommend to clean the DPF/GPF and injection system at least once a year. Recommended for all combustion engines including the newest generations with high-pressure injection and directly injected with EGR, Diesel/Gasoline Particle Filter and catalyser. Can be used in truck, tractor, construction, standalone and car engines. Biofuel compatible.

DIRECTIONS OF USE

Preventive: Add one can (1L) to the fuel before filling up to of 70 litres of fuel. Repeat this treatment yearly or every 15.000 km.

Curative: Add the content (1L) to the tank and add fuel until it contains 30L to 50L of fuel. Drive the vehicle several times at high load and high revs (>3000 rpm) in order to heat the exhaust, turbo and after treatment systems.

TYPICALS

 $\begin{array}{lll} \mbox{Physical state} & \mbox{Liquid} \\ \mbox{Colour} & \mbox{Amber} \\ \mbox{Boiling point} & 187 \ ^{\circ}\mbox{C} < - > 240 \ ^{\circ}\mbox{C} \end{array}$

Flash point 61 °C
Auto ignition temperature 255 °C
Density at 20 °C 0.79 kg/L
Water solubility at 20 °C Not

PACKAGING

1L can (12 x 1L / carton)

Ref. 3574001



